



02-09-00
HAVERSTOCK & OWENS LLP
260 Sheridan Avenue, Suite 420
Palo Alto, California 94306
(650) 833-0160

A

BOX NEW PATENT APPLICATION
Assistant Commissioner for Patents
Washington, D.C. 20231

Attorney Docket No.: SLM-04300

NEW APPLICATION TRANSMITTAL

Sir:

Transmitted herewith for filing is the patent application of Inventor: Jahja I. Trisnadi

Title: METHOD AND APPARATUS FOR REDUCING LASER SPECKLE USING POLARIZATION AVERAGING

CERTIFICATION UNDER 37 CFR § 1.10

I hereby certify that this New Application and the documents referred to as enclosed herein are being deposited with the United States Postal Service on this date, February 7, 2000, in an envelope bearing "Express Mail Post Office To Addressee" Mailing Label Number EL454481010US addressed to: **PATENT APPLICATION**, Assistant Commissioner for Patents, Washington, D.C. 20231.

Carleen O'Brien
(Name of Person Mailing Paper)

Signature

Enclosed are:

The papers required for filing date under CFR § 1.53(b):

34 Pages of Specification (including claims); 13 Sheet(s) of Drawings.
X Formal
- Informal
X Declaration or Oath
X Power of Attorney by Assignee
X Assignment of the Invention to Silicon Light Machines (including Form PTO-1595).

Fee Calculation

- Amendment changing number of claims or deleting multiple dependencies is enclosed.

CLAIMS AS FILED

	Number Filed	Number Extra	Rate	Basic Fee
				\$690.00
Total Claims	68 - 20 =	48	\$18.00	864.00
Independent Claims	12 - 3 =	9	\$78.00	702.00
Multiple Dependent claim(s), if any			\$260.00	
Filing Fee Calculation				\$2,256.00

6. X Verified Statement (Declaration) Claiming Small Entity Status

50% Filing Fee Reduction (if applicable) \$1,128.00

7. Other Fees

X Assignment Recordation Fee 40.00

- Other 0.00

TOTAL FEES ENCLOSED \$1,168.00

8. Payment of Fees

X Check in the amount of \$1,168.00 (\$1,128.00 Basic Filing Fee plus \$40.00 Assignment Recordation Fee) enclosed.

9. X Authorization to Charge Additional Fees

The Commissioner is hereby authorized to charge any additional fees (or credit any overpayment) associated with this communication and which may be required under 37 CFR § 1.16 or § 1.17 to Account No. 08-1275. **An originally executed duplicate of this transmittal is enclosed for this purpose.**

10. X Return Receipt Postcard

Dated: February 7, 2000

By:

Name: Thomas B. Haverstock
Registration No.: 32,571

Applicant Or Patentee: Jahja I. Trisnadi
 Serial or Patent No.:
 Filed or Issued: herewith
 Entitled: METHOD AND APPARATUS FOR REDUCING LASER SPECKLE USING POLARIZATION AVERAGING

**VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY
 STATUS (37 CFR § 1.9(c)) - SMALL BUSINESS CONCERN**

I hereby declare that I am

X the owner of the small business concern identified below:
 an official of the small business concern empowered to act on behalf of the concern identified below:

Name of Concern: **Silicon Light Machines**
 Address of Concern: **385 Moffett Park Dr., Suite 115
 Sunnyvale, CA 94089**

I hereby declare that the above-identified small business concern qualifies as a small business concern as defined in 13 CFR §§ 121.3-18, and reproduced in 37 CFR § 1.9(d), for purposes of paying reduced fees under Sections 41(a) and (b) of Title 35, United States Code, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both.

I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention entitled **METHOD AND APPARATUS FOR REDUCING LASER SPECKLE USING POLARIZATION AVERAGING** by inventor(s) Jahja I. Trisnadi as described in:

X the specification filed herewith
 — Application Serial No. , filed
 — Patent No. , issued

If the rights held by the above-identified small business concern are not exclusive, each individual, concern or organization having rights to the invention is listed below* and no rights to the invention are held by any person, other than the inventor, who could not qualify as a small business concern under 37 CFR § 1.9(d) or by any concern which would not qualify as a small business concern under 37 CFR § 1.9(d) or a nonprofit organization under 37 CFR § 1.9(e).

*NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR § 1.27).

Full Name: _____
 Address: _____
☐ Individual ☐ Small Business Concern ☐ Nonprofit Organization

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR § 1.28(b)).

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

Name of Person Signing: David B. Corbin

Title in Organization: President

Address of Person Signing: Silicon Light Machines, 385 Moffett Park Dr., Suite 115, Sunnyvale, CA 94089

Dated: 2/4/00

Signature: Dave B Corbin

PATENT

Attorney Docket No.: SLM-04300

**METHOD AND APPARATUS FOR REDUCING LASER SPECKLE
USING POLARIZATION AVERAGING**FIELD OF THE INVENTION

The present invention relates to the field of coherently illuminated systems. More particularly, the present invention relates to the field of reducing speckle in laser illuminated systems.

BACKGROUND OF THE INVENTION

Coherent light illuminating a rough surface produces speckle. Reflection from the rough surface is referred to as diffuse reflection. Transmission through the rough surface is referred to as diffuse transmission. In the diffuse reflection or the diffuse transmission, light scatters in various directions. The coherent light scattered by the diffuse reflection or by the diffuse transmission forms an interference pattern in the space away from the rough surface. If viewed by a human eye, the eye will see dark and light in a 'granular' pattern. The granular pattern is the speckle. An intensity detector of an optical system will also detect the speckle if the optical system views the rough surface illuminated by the coherent light.

A first speckle demonstration apparatus of the prior art is illustrated in FIG. 1. The first speckle demonstration apparatus 1 includes a first demonstration laser 2, a first diverging lens 4, and a first viewing screen 6, which are located on a first optic axis 8. The first demonstration laser 2 emits a first laser beam 10. The first diverging lens 4 transforms the first laser beam 10 into a divergent laser beam 12. The divergent laser beam 12 illuminates the first viewing screen 6 in a first large area 14. The first viewing screen 6 diffusely reflects the divergent laser beam 12 creating an interference pattern. An observation plane 16 located on a second optic axis 18 intersects the interference pattern. The observation plane 16 is the field-of-view in space where the eye or the optical system is focused. Note that the diverging lens 4 aids in demonstrating the speckle but is not necessary to produce the speckle.

FIG. 2 is a photograph of a typical speckle pattern 17 of the prior art, which is illustrative of the speckle viewed at the observation plane 16. Constructive interference of the divergent laser beam 12 reflecting diffusely from the viewing screen 6 creates bright spots in the observation plane 16. Destructive interference creates dark spots between the bright spots. The diffuse reflection from the viewing screen 6 has a random nature so the bright spots and the dark spots vary throughout the observation plane 16.

A measure of the speckle is contrast (C). The contrast, in percent, is given by $C = 100 * I_{\text{RMS}} / \bar{I}$ where \bar{I} is a mean intensity and I_{RMS} is a root mean square intensity fluctuation about the mean intensity.

Goodman in "Some fundamental properties of speckle" (J. Opt. Soc. A., vol. 66, no. 11, Nov. 1976, pp 1145-1150) teaches that the speckle can be reduced by superimposing N uncorrelated speckle patterns. This reduces the contrast by $1/\sqrt{N}$ provided that the N uncorrelated speckle patterns have equal mean intensities and contrasts. If the N uncorrelated speckle patterns have non-equal mean intensities or non-equal contrasts, the speckle reduction factor will be greater than $1/\sqrt{N}$. Thus, the $1/\sqrt{N}$ reduction factor is a best case for the speckle reduction for the N uncorrelated speckle patterns.

Goodman further teaches that the uncorrelated speckle patterns can be obtained by means of time, space, frequency, or polarization. For example, the space means could be produced by a second demonstration laser, operating at the same wavelength as the first demonstration laser 2, and a second diverging lens located on a third optic axis that illuminates the first large area 14 of the first viewing screen 6. Provided that the first optic axis 8 and the third optic axis are separated by a sufficient angle, the speckle will be reduced by $1/\sqrt{2}$. Angular separation is necessary because, if the second demonstration laser having a second laser beam is configured such that the first laser beam 10 and the second laser beam coincide, there will be no reduction in

the speckle provided that the time, frequency, or polarization means are not employed. This is because the first demonstration laser 2 and the second demonstration laser produce the same speckle patterns when the angular separation is not present. This is despite the fact that the first demonstration laser 2 is incoherent with the second demonstration laser.

Goodman further teaches that the polarization means could be a depolarizing screen, which reflects or transmits polarized light as randomly polarized diffuse light. The speckle pattern produced by the depolarizing screen differs significantly if viewed through a polarization analyzer while rotating the polarization analyzer. This indicates that two orthogonal polarization components illuminating the depolarizing screen produce two uncorrelated speckle patterns. Thus, if the viewing screen 6 is a 100% depolarizing screen, the contrast is reduced by $1/\sqrt{2}$.

Another method known in the art for creating multiple speckle patterns is to move the viewing screen 6 in an oscillatory motion 19, which employs the time means taught by Goodman. The oscillatory motion 19 typically follows a small circle or a small ellipse about the optic axis 8. This causes the speckle pattern to shift relative to the eye or the optical system viewing the viewing screen and, thus, forms multiple speckle patterns over time. Though the amount of the speckle at any instant in time is unchanged, the eye perceives the reduced speckle provided that the speed of the oscillatory motion is above a threshold speed. The intensity detector of the optical system detects the reduced speckle provided that an exposure time is sufficiently long to allow the speckle pattern to move a significant distance.

A second speckle demonstration apparatus of the prior art is illustrated in FIG. 3. The second speckle demonstration apparatus 20 includes a third demonstration laser 22, a cylindrical divergent lens 24, a scanning mirror 26, and a second viewing screen 28. The third demonstration laser 22 emits a third laser beam 30, which is coupled to the cylindrical divergent lens 24. The cylindrical divergent lens 24

5 transforms the third laser beam into a second divergent laser beam 32. The scanning mirror 26 reflects the second divergent laser beam 32. Thus, the second divergent laser beam 32 forms a line illumination 33 on the second viewing screen 28. The scanning mirror 26 repeatedly scans the line illumination 33 across a portion of the second viewing screen 28 with a scanning motion 34 having a scanning frequency. Thus, a second large area 36 is illuminated. If the eye or the optical system views the second viewing screen 28, the eye or the intensity detector will detect illumination across the second viewing screen 28 provided that the scanning frequency is sufficiently high. The eye or the intensity detector will also detect the speckle.

10 Speckle is a considerable problem in many laser illuminated systems. This difficulty is exacerbated by a relatively slow reduction in the contrast due to the $1/\sqrt{N}$ reduction factor. What is needed are additional methods of reducing laser speckle.

SUMMARY OF THE INVENTION

15 The present invention is a method and apparatus for reducing speckle using polarization averaging. A polarizing beam splitter is configured to split a first polarized laser output into a second polarized laser output and a third polarized laser output. A plurality of mirrors creates an optical path difference between the second polarized laser output and the third polarized laser output. The optical path difference is at least about a coherence length of the first polarized laser output. The second polarized laser output and the third polarized laser output are combined into a fourth laser output. The fourth laser output illuminates a depolarizing screen. If an optical system having an intensity detector or an eye views the depolarizing screen, the intensity detector or the eye will detect reduced speckle. The reduced speckle is due to an averaging effect caused by uncorrelated speckle patterns created by the second polarized laser output and the third polarized laser output.

20

25

5 A first alternative embodiment of the invention functions without the optical path difference being at least about the coherence length. In the first alternative embodiment, a piezoelectric transducer driven at a sufficient frequency varies the optical path difference by an odd multiple of a half wavelength of the first laser output. Varying the optical path difference with the sufficient frequency provides the uncorrelated speckle patterns. Thus, the intensity detector or the eye will detect the reduced speckle.

10 A second alternative embodiment employs the polarizing beam splitter, first and second quarter wave plates, first and second mirrors, and the piezoelectric transducer. The polarizing beam splitter splits the first polarized laser output into a fifth polarized laser output and a sixth polarized laser output each having linear polarizations. The first and second quarter wave plates convert the linear polarizations to circular polarizations. The first and second mirrors reflect the fifth polarized laser output and the sixth polarized laser output. The first and second quarter wave plates then convert the circular polarizations to the linear polarizations having rotated original polarizations by 90°. The piezoelectric transducer, coupled to the first mirror, varies an optical path length for the fifth polarized laser output by the odd multiple of the half wavelength of the first polarized laser output. The polarizing beam splitter combines the fifth polarized laser output and the sixth polarized laser output into a seventh laser output, which illuminates the depolarizing screen. By varying the optical path length with the sufficient frequency, the intensity detector or the eye will detect the reduced speckle.

20 A third alternative embodiment combines two orthogonally polarized laser outputs, from two lasers, into a combined laser output. The combined laser output illuminates the depolarizing screen.

A fourth alternative embodiment rotates a polarization of the first laser output with a rotation frequency to form a rotating polarization. The first laser output having the rotating polarization illuminates the depolarizing screen.

5 BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates an apparatus for demonstrating laser speckle of the prior art.

FIG. 2 is a photograph of a typical laser speckle pattern of the prior art.

FIG. 3 illustrates a second apparatus for demonstrating laser speckle of the prior art.

FIG. 4 illustrates an isometric view of the preferred embodiment of the present invention.

FIG. 5 illustrates a polarizing beam splitter of the present invention.

FIG. 6 illustrates a laser and a half wave plate of the present invention.

FIG. 7 illustrates a plan view of the preferred embodiment of the present invention.

FIG. 8 illustrates a first alternative embodiment of the present invention.

FIG. 9 illustrates a second alternative embodiment of the present invention.

FIG. 10 illustrates a third alternative embodiment of the present invention.

FIG. 11 illustrates a fourth alternative embodiment of the present invention.

FIG. 12 illustrates a fifth alternative embodiment of the present invention.

FIG. 13 illustrates a sixth alternative embodiment of the present invention.

FIG. 14 illustrates a seventh alternative embodiment of the present invention.

FIG. 15 illustrates an eighth alternative embodiment of the present invention.

FIG. 16 illustrates a ninth alternative embodiment of the present invention.

FIG. 17 illustrates a tenth alternative embodiment of the present invention.

[illegible]

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The present invention is based on the discovery that two orthogonally polarized laser outputs, which are incoherent, will produce four uncorrelated speckle patterns when illuminating a depolarizing screen.

5 The preferred embodiment of the present invention is illustrated in FIG. 4. The preferred embodiment 37 includes a first laser 38, a half wave plate 80, a polarizing beam splitter 40, and the depolarizing screen 42, which are located on an optic axis 44. The first laser 38, having a coherence length, emits a first polarized laser output 46, which is a linearly polarized collimated beam. The first polarized laser output 46 is coupled to the polarizing beam splitter 40. The polarizing beam splitter 40 divides the first polarized laser output 46 into a second polarized laser output 48 and a third polarized laser output 49. The third polarized laser output 49 continues along the optic axis 44. The second polarized laser output 48 is reflected by a first mirror 50, a second mirror 52, a third mirror 54, and a fourth mirror 56. The first, second, third, and fourth mirrors 50, 52, 54, and 56 define a light guide. It will be readily apparent to one of ordinary skill in the art that more or fewer mirrors can be used to accomplish the objectives of the present invention.

10 After reflecting from the fourth mirror 56, the second polarized laser output 48 is reflected by the polarizing beam splitter 40, which combines the second polarized laser output 48 and the third polarized laser output 49 into a fourth laser output 58. By transmitting the second polarized laser output through the light guide, the second polarized laser output 48 has been shifted relative to the third polarized laser output 49 by an optical path difference. The fourth laser output 58 is then coupled to the depolarizing screen 42. The depolarizing screen 42 reflects or transmits the fourth laser output as randomly polarized diffuse light. If the depolarizing screen 42 reflects the fourth laser output 58, the depolarizing screen 42 comprises a diffuse reflecting screen. If the depolarizing screen 42 transmits the

fourth laser output 58, the depolarizing screen 42 comprises a diffuse transmitting screen. An intensity detector of an optical system or an eye viewing the depolarizing screen 42 will detect reduced speckle provided that the optical path difference is at least a sufficient distance.

5 Preferably, the sufficient distance is the coherence length. Alternatively, the sufficient distance is less than the coherence length but reduction in the speckle will be less than if the sufficient distance is at least the coherence length.

10 A first partial view 59 of FIG. 4 is further illustrated in FIG. 5. The first partial view 59 includes the polarizing beam splitter 40, the first and second polarized laser outputs, 46 and 48, and the fourth laser output 58. The first polarized laser output 46 has a first linear polarized E (electric) field 60. The first linear polarized E field 60 is a combination of a second linear polarized E field 62 and a third linear polarized E field 64, which are orthogonal polarizations of the first linear polarized E field 60. Preferably, the second linear polarized E field 62 and the third linear polarized E field 64 have equal amplitudes. In the preferred embodiment 37 (FIG. 4) the equal amplitudes are obtained by rotating the half wave plate 80 about the optic axis 44.

15 Referring to FIG. 5, the second linear polarized E field 62 is vertical and the third linear polarized E field 64 is horizontal. The polarizing beam splitter 40 reflects the first polarized laser output 46 having the second linear polarized E field 62 from a polarizing beam splitting reflector 66 while allowing the first polarized laser output having the third linear polarized E field 64 to pass through the polarizing beam splitting reflector 66. Thus, the second polarized laser output 48 is the first polarized laser output 46 having the second linear polarized E field 62. Also, the third polarized laser output 49 is the first polarized laser output 46 having the third linear polarized E field 64.

The first polarized laser output 46 and the second polarized laser output 48 define a plane of incidence relative to the polarizing beam splitting reflector 66. It is a convention of optics to refer to the second linear polarized E field 62 as an s-polarization and the third linear polarized E field 64 as a p-polarization, where the s indicates perpendicular to the plane of incidence and the p indicates parallel to the plane of incidence. It will be readily apparent to one skilled in the art that the first linear polarized E field 60 could be replaced by a circularly polarized E field.

A second partial view 79 of FIG. 4 is further illustrated in FIG. 6. The second partial view 79 includes the first laser 38 and the half wave plate 80. A rotation 82 of the half wave plate 80 about the optic axis 44 rotates the first linear polarized E field 60 such that a polarization angle 83 is adjusted. The rotation 82 is used to equalize the amplitudes of the second linear polarized E field 62 and the third linear polarized E field 64. It will be readily apparent to one skilled in the art that the half wave plate 80 can be eliminated since the amplitudes of the second and third linear polarized E fields, 62 and 64, can be equalized by rotating the first laser 38.

A plan view of the preferred embodiment 37 is illustrated in FIG. 7, including the polarizing beam splitter 40 and the first, second, third, and fourth mirrors 50, 52, 54, and 56, which are defined as a speckle reducing arrangement 68. The polarizing beam splitter 40 divides the first polarized laser output 46 into the second polarized laser output 48 and the third polarized laser output 49. The second polarized laser output 48 travels a first optical path length 70 from the polarizing beam splitting reflector 66 to the first mirror 50. The second polarized laser output 48 travels a second optical path length 72 from the first mirror 50 to the second mirror 52. The second polarized laser output 48 travels a third optical path length 74 from the second mirror 52 to the third mirror 54. The second polarized laser output 48 travels a fourth optical path length 76 from the third mirror 54 to the fourth mirror 56. The second polarized laser output 48 travels a fifth optical path length 78 from the fourth

mirror 56 to the polarizing beam splitting reflector 66. The first, second, third, fourth, and fifth optical path lengths, 70, 72, 74, 76, and 78, are optical path lengths, each of which is a summation of geometric length times index of refraction.

5 The first, second, third, fourth, and fifth optical path lengths 70, 72, 74, 76, and 78 define the optical path difference. It will be readily apparent to one skilled in the art that the second, third, and fourth optical path lengths 72, 74, and 76 may, but do not necessarily, lie in a plane defined by the first polarized laser output 46, the first optical path length 70, and the fifth optical path length 78.

10 After the second polarized laser output 48 traverses the optical path difference, the polarizing beam splitting reflector 66 reflects the second polarized laser output 48 such that the second polarized laser output 48 and the third polarized laser output 49 combine to form the fourth laser output 58. The fourth laser output 58 illuminates the depolarizing screen 42. Preferably, the optical path difference is equal to or greater than the coherence length for the first laser 38. As a result, the speckle produced by the p-polarization and the s-polarization are incoherent. Alternatively, the optical path difference is less than the coherence length but this results in less speckle reduction because the p-polarization and the s-polarization are partially coherent.

20 The depolarizing screen 42 produces first and second speckle patterns from the p-polarization, which are uncorrelated. The depolarizing screen 42 also produces third and fourth speckle patterns from the s-polarization, which are uncorrelated. For the optical path difference being at least the coherence length, the first, second, third, and fourth speckle patterns are uncorrelated because the s-polarization and p-polarization are incoherent. Thus, the speckle reducing arrangement 68 and the depolarizing screen 42 produce a total of four uncorrelated speckle patterns. Speckle is theoretically reduced by a speckle reduction factor of $1/\sqrt{4} = 1/2$. The speckle reduction factor of 1/2 is a combination of the depolarizing screen 42, which

contributes a $1/\sqrt{2}$ factor, and the speckle reducing arrangement 68, which contributes an additional $1/\sqrt{2}$ factor.

For the optical path difference being less than the coherence length, there is a partial correlation between the first and third speckle patterns and between the second and fourth speckle patterns since the p-polarization and the s-polarization are partially coherent. In this case the speckle reduction factor will be between $1/\sqrt{2}$ and $1/2$.

A first alternative embodiment of the present invention is illustrated in FIG. 8. The first alternative embodiment 84 includes a fifth mirror 85, a sixth mirror 86, and a seventh mirror 88. The fifth, sixth, and seventh mirrors, 85, 86, and 88, form the light guide, which provides the optical path difference for the second polarized laser output 48.

A second alternative embodiment of the present invention is illustrated in FIG. 9. The second alternative embodiment 90 includes a polarization preserving fiber optic 92, which forms the light guide providing the optical path difference for the second polarized laser output 48.

A third alternative embodiment of the present invention is illustrated in FIG. 10. The third alternative embodiment 93 includes the first laser 38, the half wave plate 80, the speckle reducing arrangement 68, a cylindrical divergent lens 94, a scanning mirror 96, and a second depolarizing screen 100. The cylindrical divergent lens transforms the fourth laser output 58 into a divergent laser beam 98. The scanning mirror reflects the divergent laser beam 98 onto the depolarizing screen 42 and, thus, forms a line illumination on the depolarizing screen 42. The scanning mirror scans the line illumination across the second depolarizing screen 100 with a sawtooth scan motion. The sawtooth scan motion has two components. In a first scan motion 102, the scanning mirror scans the line illumination 98 across the second depolarizing screen 100. In a second scan motion 104, the scanning mirror returns to the start of the first scan motion 102. The second scan motion 104 is much faster

than the first scan motion 102. The sawtooth scan motion alternately repeats the first scan motion 102 and the second scan motion 104. Thus, the first scan motion 102 provides a predominant illumination of the second depolarizing screen 100. It will be readily apparent to one skilled in the art that other scan motions or sequences may be used to illuminate the second depolarizing screen 100.

In the third alternative embodiment 93, the speckle is reduced by the four uncorrelated speckle patterns. The four uncorrelated speckle patterns are due to the combination of the second depolarizing screen 100 and the optical path difference, which is provided by the speckle reducing arrangement 68.

If the first laser 38 has a long coherence length it may be difficult or impractical to make the optical path difference equal to or greater than the coherence length of the first laser 38. A fourth alternative embodiment of the present invention, which accounts for the long coherence length, is illustrated in FIG. 11. The fourth alternative embodiment 105 adds a piezoelectric transducer 106 to the preferred embodiment. In the fourth alternative embodiment 105, the piezoelectric transducer 106 is coupled to the fourth mirror 56. It will be readily apparent to one skilled in the art that the piezoelectric transducer 106 may be coupled to the first, second or third mirror, 50, 52, or 54, or that the piezoelectric transducer 106 may be coupled to multiple mirrors.

In the fourth alternative embodiment 105, the piezoelectric transducer 106 moves the fourth mirror 56 such that the optical path difference is varied by an amplitude. By varying the optical path difference with a sufficient frequency, the third and fourth speckle patterns shift relative to the first and second speckle patterns and the eye, or the intensity detector, detects the reduced speckle. The sufficient frequency is determined by an integration time for the eye or the intensity detector. A first electrical signal 108 drives the piezoelectric transducer 94. The first electrical signal 108 is preferably an oscillating voltage driven at the sufficient frequency. It

will readily apparent to one skilled in the art that other electrical signals may be used to drive the piezoelectric transducer 106 including a randomly fluctuating signal.

Preferably, the electrical signal 108 is a square wave signal. For the square wave signal, the amplitude is preferably an odd multiple of a half wavelength of the first polarized laser output 46. Alternatively, the electrical signal 108 is a non-square wave signal, such as a sinusoidal signal. For the non-square wave signal, the amplitude is preferably at least the half wavelength of the first polarized laser output 46.

A fifth alternative embodiment of the present invention is illustrated in FIG. 12. The fifth alternative embodiment 109 adds the piezoelectric transducer 106 to the third alternative embodiment 93. In the fifth alternative embodiment 109, the optical path difference is not necessarily equal to or greater than the coherence length. In the fifth alternative embodiment 109, the piezoelectric transducer 106 varies the optical path difference by the odd multiple of the half wavelength of the first polarized laser output 46. In the fifth alternative embodiment 109, a second electrical signal 110 drives the piezoelectric transducer 106. The second electrical signal 110 is a square wave voltage having a first voltage level, a second voltage level, and a square wave period. A difference between the first voltage level and the second voltage level shifts the optical path difference by the odd multiple of the half wavelength. The square wave period is one cycle of the first voltage level and the second voltage level.

In the fifth alternative embodiment 109, the first scan motion 102 and the second scan motion 104 is defined as a scan period. For a first scan period, the square wave voltage has the first voltage level. For a second scan period, immediately following the first scan period, the square wave voltage has the second voltage level. For subsequent scans, the square wave period corresponds to two scan periods such that, for a third scan period, the square wave voltage has the first

voltage level and, for a fourth scan period, the square wave voltage has the second voltage level. Thus, the third and fourth uncorrelated speckle patterns shift relative to the first and second uncorrelated speckle patterns in each pair of scan periods. The speckle is reduced by a combination of the depolarizing screen 100, the sawtooth scan motion, and the shifting third and fourth uncorrelated speckle patterns.

A sixth alternative embodiment of the present invention is illustrated in FIG. 13. The sixth alternative embodiment 111 adds a second laser 112 to the first laser 38, the polarizing beam splitter 40, and the depolarizing screen 42. The first laser 38 is configured such that the first polarized laser output 46 has an E field oriented in a p-polarization relative to the polarizing beam splitting reflector 66. The second laser 112 is configured such that a fifth polarized laser output 114 has an E field oriented in an s-polarization relative to the polarizing beam splitting reflector 66. The polarizing beam splitting reflector 66 includes multilayered dielectrics that reflect the s-polarization and transmit the p-polarization. The first polarized laser output 46 passes through the polarizing beam splitting reflector 66. The fifth polarized laser output 114 reflects from the polarizing beam splitting reflector 66.

In the sixth alternative embodiment 111, the first polarized laser output 46 and the fifth polarized laser output 114 combine to form a combined laser output 115. The combined laser output 115 illuminates the depolarizing screen 42. Since the first laser 38 and the second laser 112 are incoherent with each other, the combined laser output 115 produces four uncorrelated speckle patterns upon illumination of the depolarizing screen 42. It will be readily apparent to one skilled in the art that the polarizing beam splitter 40 could be replaced by a device that functions similarly to the multilayered dielectrics of the polarizing beam splitting reflector 66.

A seventh alternative embodiment of the present invention is illustrated in FIG. 14. The seventh alternative embodiment 116 includes the first laser 38, the half wave plate 80, the polarizing beam splitter 40, the first and second mirrors, 50 and 52, the

depolarizing screen 42, the piezoelectric transducer 106, the first electrical signal 108, and first and second quarter wave plates, 118 and 120. The polarizing beam splitter 40 divides the first polarized laser output 46 into sixth and seventh polarized laser outputs, 122 and 124, having the p-polarization and the s-polarization, respectively. The first and second quarter wave plates, 118 and 120, have first and second optic axes oriented at 45° to the p-polarization and the s-polarization of the sixth and seventh polarized laser outputs, 122 and 124, respectively. The first and second quarter wave plates, 118 and 120, convert the p-polarization and the s-polarization polarizations of the sixth and seventh polarized laser outputs, 122 and 124, respectively, to circular polarizations. The first and second mirrors, 50 and 52, reflect the sixth and seventh polarized laser outputs, 122 and 124. The piezoelectric transducer 106, driven by the first electrical signal 108, varies a sixth optical path length for the sixth polarized laser output 122 by the amplitude. The first electrical signal 108 is preferably the oscillating voltage driven at the sufficient frequency.

Upon the sixth and seventh polarized laser outputs, 122 and 124, returning to the first and second quarter wave plates, 118 and 120, the first and second quarter wave plates, 118 and 120, convert the sixth and seventh polarized laser outputs, 122 and 124, to the s-polarization and the p-polarization, respectively. The polarizing beam splitter 40 reflects the sixth polarized laser output 122 and transmits the seventh polarized laser output 124, thus forming an eighth laser output 126, which illuminates the depolarizing screen 42. The speckle is reduced by two pairs of uncorrelated speckle patterns, which are further uncorrelated by varying the sixth optical path length by the amplitude.

An eighth alternative embodiment is illustrated in FIG. 15. The eighth alternative embodiment 130 includes the first and second lasers, 38 and 112, a birefringent crystal 132, and the depolarizing screen 42. The first laser 38 has a fourth linear polarized E field 134. The second laser 112 has a fifth linear polarized

E field 136. The birefringent crystal 132 is oriented such that the first polarized laser output 46 becomes an extraordinary ray within the birefringent crystal 132 and further such that the fifth polarized laser output 114 becomes an ordinary ray within the birefringent crystal 132. Upon exiting from the birefringent crystal 132, the first and fifth polarized laser outputs, 46 and 114, have combined to form the combined laser output 115. The combined laser output 115 illuminates the depolarizing screen 42.

A ninth alternative embodiment is illustrated in FIG. 16. The ninth alternative embodiment 140 includes the first laser 38, a polarization rotator 142, and the depolarizing screen 42. In the ninth alternative embodiment 140, the polarization rotator 142 is driven by a third electrical signal 144. The polarization rotator 142 rotates a polarization of the first polarized laser output 46 to form a ninth laser output 146 having a rotating polarization. The ninth laser output illuminates the depolarizing screen 42. The ninth laser output 146 having the rotating polarization produces the four uncorrelated speckle patterns. Provided that a rotation frequency is sufficient, the eye or the intensity detector averages the four uncorrelated speckle patterns and, thus, the eye or the intensity detector detects the reduced speckle. The polarization rotator 142 is preferably an electro-optic polarization rotator such as a liquid crystal polarization rotator, a Pockels cell, or a Kerr cell. Alternatively, the polarization rotator is a half wave plate that is mechanically rotated.

A tenth alternative embodiment of the present invention is illustrated in FIG. 17. The tenth alternative embodiment 150 includes the first laser 38, the half wave plate 80, the polarizing beam splitter 40, the first and second mirrors, 50 and 52, the depolarizing screen 42, and the first and second quarter wave plates, 118 and 120. The polarizing beam splitter 40 divides the first polarized laser output 46 into a tenth polarized laser output 152 and an eleventh polarized laser output 154 having the p-polarization and the s-polarization, respectively. The polarizing beam splitter 40 transmits the tenth polarized laser output 152 toward the first quarter wave plate 118.

The polarizing beam splitter reflects the eleventh polarized laser output 154 toward the depolarizing screen 42.

5 The first quarter wave plate 118 has the first optic axis oriented at 45° to the p-polarization of the tenth polarized laser output 152. The first quarter wave plate 118 converts the p-polarization of the tenth polarized laser output 152 to the circular polarization. The first mirror 50 reflects the tenth polarized laser output 152. Upon the tenth polarized laser output 152 returning to the first quarter wave plate 118, the first quarter wave plate converts the circular polarization to the s-polarization. Thus, the tenth polarized laser output 152 travels a seventh optical path length from the polarizing beam splitter reflector 66 to the first mirror 50 and back to the polarizing beam splitter reflector 66. The polarizing beam splitter 40 then reflects the tenth polarized laser output 152 toward the second quarter wave plate 120.

10 The second quarter wave plate 120 has the second optic axis oriented at 45° to the s-polarization of the tenth polarized laser output 152. The second quarter wave plate 120 converts the s-polarization of the tenth polarized laser output 152 to the circular polarization. The second mirror 52 reflects the tenth polarized laser output 152. Upon the tenth polarized laser output 152 returning to the second quarter wave plate 120, the second quarter wave plate 120 converts the circular polarization to the p-polarization. Thus, the tenth polarized laser output 152 travels an eighth optical path length from the polarizing beam splitter reflector 66 to the second mirror 52 and back to the polarizing beam splitter reflector 66.

20 The polarizing beam splitter 40 transmits the tenth polarized laser output 152 and, thus, combines the tenth polarized laser output 152 and the eleventh polarized laser output 154 to form the fourth laser output 58 having the optical path difference between the tenth polarized laser output 152 and the eleventh polarized laser output 154. The seventh and eighth optical path lengths define the light guide for the optical path difference. Preferably, the optical path difference is at least the coherence

length. The fourth laser output 58 illuminates the depolarizing screen 42 and, thus, the speckle is reduced by the four uncorrelated speckle patterns.

It will be readily apparent to one skilled in the art that in the tenth alternative embodiment 150, the first and second quarter wave plates, 118 and 120, can be eliminated by configuring the first mirror 50 to reflect the tenth polarized laser output 152 to the second mirror 52 and configuring the second mirror 52 to reflect the tenth polarized laser output 152 to the polarizing beam splitter 66.

First and second tests were performed using a first test arrangement similar to the preferred embodiment 37. In the first test, the speckle reducing arrangement 68 was not present. In the second test, the speckle reducing arrangement 68 was present. Theoretically, the speckle reducing arrangement 68 should reduce the contrast by a reduction factor of $.707 = 1/\sqrt{2}$ since the speckle reducing arrangement 68 doubles the number of uncorrelated speckle patterns. In the first test, the contrast was found to be 56.8%. In the second test, the contrast was found to be 42.2%. This amounted to a reduction factor of .743, which is close to the theoretical limit of .707.

It will be readily apparent to one skilled in the art that other various modifications may be made to the preferred embodiment without departing from the spirit and scope of the invention as defined by the appended claims.

CLAIMS

I claim:

1. An apparatus for reducing laser speckle comprising:
 - a. a polarizing beam splitter configured to divide a first polarized laser output into a second polarized laser output and a third polarized laser output, the first polarized laser output having a coherence length;
 - b. a light guide configured to create an optical path difference between the second polarized laser output and the third polarized laser output, the optical path difference being at least about the coherence length, the light guide being configured to direct the second polarized laser output to the polarizing beam splitter such that the polarizing beam splitter combines the second polarized laser output and the third polarized laser output into a fourth laser output; and
 - c. a depolarizing screen coupled to the fourth laser output, the fourth laser output illuminating the depolarizing screen.
2. The apparatus of claim 1 wherein the light guide comprises a plurality of mirrors.
3. The apparatus of claim 2 further comprising a half wave plate coupled to the first polarized laser output, the half wave plate being configured to adjust a first polarization angle for the first polarized laser output such that the second polarized laser output and the third laser output have intensities that are about equal.

1 4. The apparatus of claim 3 wherein the depolarizing screen comprises a
2 diffuse reflecting surface.

1 5. The apparatus of claim 4 further comprising a laser for providing the
2 first polarized laser output.

1 6. The apparatus of claim 3 wherein the depolarizing screen comprises a
2 diffuse transmitting surface.

1 7. The apparatus of claim 6 further comprising a laser for providing the
2 first polarized laser output.

1 8. The apparatus of claim 2 further comprising a laser for providing the
2 first polarized laser output, the laser being configured such that intensities of the
3 second polarized laser output and the third polarized laser output are about equal.

1 9. The apparatus of claim 8 wherein the depolarizing screen comprises a
2 diffuse reflecting surface.

1 10. The apparatus of claim 8 wherein the depolarizing screen comprises a
2 diffuse transmitting surface.

1 11. The apparatus of claim 1 wherein the light guide comprises a
2 polarization preserving fiber optic.

1 12. The apparatus of claim 1 wherein the polarizing beam splitter divides
2 the first polarized laser output by reflecting the second polarized laser output and
3 transmitting the third polarized laser output.

1 13. The apparatus of claim 12 wherein the polarizing beam splitter
2 combines the second polarized laser output and the third polarized laser output by
3 reflecting the second polarized laser output.

1 14. The apparatus of claim 1 wherein the polarizing beam splitter divides
2 the first polarized laser output by transmitting the second polarized laser output and
3 reflecting the third polarized laser output.

1 15. The apparatus of claim 14 wherein the polarizing beam splitter
2 combines the second polarized laser output and the third polarized laser output by
3 transmitting the second polarized laser output.

1 16. A method of reducing laser speckle comprising the steps of:
2 a. dividing a first polarized laser output into a second polarized
3 laser output and a third polarized laser output, the first polarized laser
4 output having a coherence length, the second polarized laser output and
5 the third polarized laser output having orthogonal polarizations and
6 having intensities that are about equal;
7 b. creating an optical path difference between the second polarized
8 laser output and the third polarized laser output, the optical path
9 difference being at least about the coherence length;
10 c. combining the second polarized laser output and the third
11 polarized laser output into a fourth laser output; and

12 d. illuminating a depolarizing screen with the fourth laser output.

1 17. The method of claim 16 wherein the depolarizing screen comprises a
2 diffuse reflecting surface.

1 18. The method of claim 16 wherein the depolarizing screen comprises a
2 diffuse transmitting surface.

19. An apparatus for reducing laser speckle comprising:

- 1 a. a polarizing beam splitter configured to divide a first polarized
2 laser output into a second polarized laser output and a third polarized
3 laser output;
4
5 b. a plurality of mirrors configured to create an optical path
6 difference between the second polarized laser output and the third
7 polarized laser output, the plurality of mirrors configured to direct the
8 second polarized laser output to the polarizing beam splitter such that
9 the polarizing beam splitter combines the second polarized laser output
10 and the third polarized laser output into a fourth laser output;
11 c. a piezoelectric transducer coupled to at least one of the mirrors,
12 the piezoelectric transducer being driven by an electrical signal such
13 that the optical path difference is varied by an amplitude, the amplitude
14 being at least about a half wavelength of the first polarized laser output,
15 the electrical signal having an electrical signal frequency; and
16 d. a depolarizing screen coupled to the fourth laser output, the
17 fourth laser output illuminating the depolarizing screen, the electrical
18 signal frequency being at least a sufficient frequency such that laser
19 speckle is reduced.

1 20. The apparatus of claim 19 further comprising a half wave plate coupled
2 to the first polarized laser output, the half wave plate being configured to adjust a first
3 polarization angle for the first polarized laser output such that the second polarized
4 laser output and the third laser output have intensities that are about equal.

1 21. The apparatus of claim 20 wherein the depolarizing screen comprises a
2 diffuse reflecting surface.

1 22. The apparatus of claim 21 further comprising a laser for providing the
2 first polarized laser output.

1 23. The apparatus of claim 20 wherein the depolarizing screen comprises a
2 diffuse transmitting surface.

1 24. The apparatus of claim 23 further comprising a laser for providing the
2 first polarized laser output.

1 25. The apparatus of claim 19 further comprising a laser for providing the
2 first polarized laser output, the laser being configured such that intensities of the
3 second polarized laser output and the third polarized laser output are about equal.

1 26. The apparatus of claim 25 wherein the depolarizing screen comprises a
2 diffuse reflecting surface.

1 27. The apparatus of claim 25 wherein the depolarizing screen comprises a
2 diffuse transmitting surface.

1 28. The apparatus of claim 19 wherein the polarizing beam splitter divides
2 the first polarized laser output by reflecting the second polarized laser output and
3 transmitting the third polarized laser output.

1 29. The apparatus of claim 28 wherein the polarizing beam splitter
2 combines the second polarized laser output and the third polarized laser output by
3 reflecting the second polarized laser output.

1 30. The apparatus of claim 19 wherein the polarizing beam splitter divides
2 the first polarized laser output by transmitting the second polarized laser output and
3 reflecting the third polarized laser output.

1 31. The apparatus of claim 30 wherein the polarizing beam splitter
2 combines the second polarized laser output and the third polarized laser output by
3 transmitting the second polarized laser output.

1 32. The apparatus of claim 19 wherein the electrical signal comprises a
2 non-square wave signal.

1 33. The apparatus of claim 19 wherein the electrical signal comprises a
2 square wave signal and further wherein the amplitude is about an odd multiple of the
3 half wavelength of the first polarized laser output.

1 34. An apparatus for reducing laser speckle:
2 a. means for dividing a first polarized laser output into a second
3 polarized laser output and a third polarized laser output, the first
4 polarized laser output having a coherence length, the second polarized

5 laser output and the third polarized laser output having orthogonal
6 polarizations and having intensities that are about equal;

- 7 b. means for oscillating an optical path length of the second
8 polarized laser output by an amplitude and with an oscillation
9 frequency, the amplitude being at least about a half wavelength of the
10 first polarized laser output;
- 11 c. means for combining the second polarized laser output and the
12 third polarized laser output into a fourth laser output; and
- 13 d. a depolarizing screen coupled to the fourth laser output, the
14 fourth laser output illuminating the depolarizing screen, the oscillation
15 frequency being at least a sufficient frequency such that laser speckle is
16 reduced.

17 35. The apparatus of claim 34 wherein the means for dividing comprises a
18 polarizing beam splitter.

19 36. The apparatus of claim 35 wherein the means for combining comprises
20 the polarizing beam splitter.

21 37. The apparatus of claim 36 wherein the means for combining further
22 comprises:

- 23 a. a first mirror coupled to the second polarized laser output, the
24 first mirror reflecting the second polarized laser output back to the
25 polarizing beam splitter;
- 26 b. a first quarter wave plate coupled to the second polarized laser
27 output between the polarizing beam splitter and the first mirror such
28 that a first polarization angle for the second polarized laser output is

rotated by ninety degrees upon the second polarized laser output
returning to the polarizing beam splitter;

c. a second mirror coupled to the third polarized laser output, the
second mirror reflecting the third polarized laser output back to the
polarizing beam splitter; and

d. a second quarter wave plate coupled to the third polarized laser
output between the polarizing beam splitter and the second mirror such
that a second polarization angle for the third polarized laser output is
rotated by ninety degrees upon the third polarized laser output returning
to the polarizing beam splitter.

38. The apparatus of claim 37 wherein the means for oscillating comprises
a piezoelectric transducer coupled to the first mirror.

39. The apparatus of claim 36 wherein the means for combining further
comprises a plurality of mirrors arranged such that the second polarized laser output
returns to the polarizing beam splitter and further such that the second polarized laser
output combines with the third polarized laser output to form the fourth laser output.

40. The apparatus of claim 39 wherein the means for oscillating comprises
a piezoelectric transducer coupled to one of the mirrors.

41. A method of reducing laser speckle comprising the steps of:

a. dividing a first polarized laser output into a second polarized
laser output and a third polarized laser output, the second polarized
laser output and the third polarized laser output having orthogonal
polarizations and having intensities that are about equal;

- 6 b. oscillating an optical path length for the second polarized laser
7 output by an amplitude and with an oscillation frequency, the amplitude
8 being at least about a half wavelength of the first polarized laser output;
9 c. combining the second polarized laser output and the third
10 polarized laser output into a fourth laser output; and
11 d. illuminating a depolarizing screen with the fourth laser output,
12 the oscillation frequency being at least a sufficient frequency such that
13 laser speckle is reduced.

42. The method of claim 41 wherein the depolarizing screen comprises a
diffuse reflecting surface.

43. The method of claim 41 wherein the depolarizing screen comprises a
diffuse transmitting surface.

44. An apparatus for reducing laser speckle comprising:

- a. means for dividing a first polarized laser output into a second
 polarized laser output and a third polarized laser output, the second
 polarized laser output and the third polarized laser output having
 orthogonal polarizations and having intensities that are about equal;
 b. means for switching between first and second optical path
 lengths for the second polarized laser output, a difference between the
 first and second optical path lengths being about an odd multiple of a
 half wavelength of the first polarized laser output;
 c. means for combining the second polarized laser output and the
 third polarized laser output into a fourth laser output;

- 12 d. means for diverging the fourth laser output in a first direction to
13 create a fifth laser output;
- 14 e. a scanning mirror coupled to the fifth laser output, the scanning
15 mirror reflecting the fifth laser output to create a line illumination; and
- 16 f. a depolarizing screen illuminated by the line illumination, the
17 scanning mirror repeatedly scanning the line illumination across a
18 portion of the depolarizing screen such that the means for switching
19 maintains the first optical path length for a first scan, switches to the
20 second optical path length for a second scan, and alternates between the
21 first and second optical path lengths for subsequent scans.

45. The apparatus of claim 44 wherein the depolarizing screen comprises a
diffuse reflecting surface.

46. The apparatus of claim 44 wherein the depolarizing screen comprises a
diffuse transmitting surface.

- 1 47. A method of reducing laser speckle comprising the steps of:
- 2 a. dividing a first polarized laser output into a second polarized
3 laser output and a third polarized laser output, the second polarized
4 laser output and the third polarized laser output having orthogonal
5 polarizations and having intensities that are about equal;
- 6 b. switching between first and second optical path lengths for the
7 second polarized laser output, a difference between the first and second
8 optical path lengths being about an odd multiple of a half wavelength of
9 the first polarized laser output;

- 10 c. combining the second polarized laser output and the third
11 polarized laser output into a fourth laser output;
12 d. diverging the fourth laser output in a first direction; and
13 e. scanning the fourth laser output in a second direction across a
14 portion of a depolarizing screen in a first scan with the first optical path
15 length, in a second scan with the second optical path length, and in
16 subsequent scans alternating between the first and second optical path
17 lengths, the second direction being orthogonal to the first direction.

48. The method of claim 47 wherein the depolarizing screen comprises a
diffuse reflecting surface.

49. The method of claim 47 wherein the depolarizing screen comprises a
diffuse transmitting surface.

50. An apparatus for reducing laser speckle comprising:

- 3 a. means for combining a first polarized laser output and a second
4 polarized laser output, the first polarized laser output being incoherent
5 with the second polarized laser output, the first polarized laser output
6 and the second polarized laser output having orthogonal polarizations,
7 whereby a third laser output is formed; and
b. a depolarizing screen coupled to the third laser output.

1 51. The apparatus of claim 50 wherein the depolarizing screen comprises a
2 diffuse reflecting surface.

1 52. The apparatus of claim 50 wherein the depolarizing screen comprises a
2 diffuse transmitting surface.

1 53. The apparatus of claim 50 wherein the means for combining comprises
2 a polarizing beam splitter.

1 54. The apparatus of claim 50 wherein the means for combining comprises
2 a multilayered dielectric device which transmits the first polarized laser output and
3 reflects the second polarized laser output.

1 55. The apparatus of claim 50 wherein the means for combining comprises
2 a birefringent crystal.

1 56. A method for reducing laser speckle comprising the steps of:
2 a. combining a first polarized laser output and a second polarized
3 laser output to form a third laser output, the first polarized laser output
4 being incoherent with the second polarized laser output, the first
5 polarized laser output and the second polarized laser output having
6 orthogonal polarizations; and
7 b. illuminating a depolarizing screen with the third laser output.

1 57. The method of claim 56 wherein the depolarizing screen comprises a
2 diffuse reflecting surface.

1 58. The method of claim 56 wherein the depolarizing screen comprises a
2 diffuse transmitting surface.

- 1 59. An apparatus for reducing laser speckle comprising:
- 2 a. means for rotating a polarization of a laser output, whereby a
- 3 rotating polarization is formed, the rotating polarization being driven
- 4 with a rotation frequency; and
- 5 b. a depolarizing screen coupled to the laser output, the rotation
- 6 frequency being sufficient to reduce laser speckle.
- 1 60. The apparatus of claim 59 wherein the means for rotating comprises an
- 2 electro-optic polarization rotator.
- 3 61. The apparatus of claim 59 wherein the means for rotating comprises a
- 4 half wave plate, the half wave plate being mechanically rotated.
- 5 62. A method for reducing laser speckle comprising the steps of:
- 6 a. rotating a polarization of a laser output, whereby a rotating
- 1 polarization is formed, the rotating polarization being driven with a
- 2 rotation frequency; and
- 3 b. illuminating a depolarizing screen with the laser output, the
- 4 rotation frequency being sufficient to reduce laser speckle.
- 5 63. An apparatus for reducing laser speckle:
- 6 a. means for dividing a first polarized laser output into a second
- 1 polarized laser output and a third polarized laser output, the first
- 2 polarized laser output having a coherence length, the second polarized
- 3 laser output and the third polarized laser output having orthogonal
- 4 polarizations and having intensities that are about equal;

- b. a light guide coupled to the second polarized laser output, the light guide creating an optical path difference between the second polarized laser output and the third polarized laser output, the optical path difference being at least about the coherence length;
- c. means for combining the second polarized laser output and the third polarized laser output into a fourth laser output; and
- d. a depolarizing screen coupled to the fourth laser output.

64. The apparatus of claim 63 wherein the means for dividing comprises a polarizing beam splitter.

65. The apparatus of claim 64 wherein the means for combining comprises the polarizing beam splitter.

66. The apparatus of claim 65 wherein the light guide further comprises:

- a. a first mirror coupled to the second polarized laser output, the first mirror reflecting the second polarized laser output back to the polarizing beam splitter;
- b. a first quarter wave plate coupled to the second polarized laser output between the polarizing beam splitter and the first mirror such that a polarization angle for the second polarized laser output is rotated by ninety degrees upon a first return of the second polarized laser output to the polarizing beam splitter;
- c. a second mirror coupled to the second polarized laser output subsequent to the first return of the second polarized laser output to the polarizing beam splitter, the second mirror reflecting the second polarized laser output back to the polarizing beam splitter; and

14 d. a second quarter wave plate coupled to the second polarized
15 laser output between the polarizing beam splitter and the second mirror
16 such that the polarization angle for the second polarized laser output is
17 rotated by ninety degrees upon the second polarized laser output
18 returning to the polarizing beam splitter.

1 67. The apparatus of claim 65 wherein the light guide comprises a plurality
2 of mirrors.

3 68. The apparatus of claim 65 wherein the light guide comprises a
4 polarization preserving fiber optic.

ABSTRACT OF THE DISCLOSURE

A method and apparatus for reducing speckle uses polarization averaging. A polarizing beam splitter divides a first polarized laser output into a second polarized laser output and a third polarized laser output. A plurality of mirrors creates an optical path difference between the second and third polarized laser outputs. The optical path difference is at least about a coherence length for the first polarized laser output. The second and third polarized laser outputs are combined into a fourth laser output, which illuminates a depolarizing screen. If a human eye or an optical system having a intensity detector views the depolarizing screen, the eye or the intensity detector will detect reduced speckle, which results from uncorrelated speckle patterns created by the second polarized laser output and the third polarized laser output. A first alternative embodiment of the invention functions without the optical path difference being at least about the coherence length. In the first alternative embodiment, a piezoelectric transducer varies an optical path length by at least about a half wavelength of the first polarized laser output. By varying the optical path length by a sufficient frequency, the eye or the intensity detector will detect the reduced speckle. A second alternative embodiment combines two orthogonally polarized laser outputs, from two lasers, into a combined laser output. The combined laser output illuminates the depolarizing screen. A third alternative embodiment rotates the first laser output with a rotation frequency to form a rotating polarized laser output, which illuminates the depolarizing screen.

17




FIG. 2
(PRIOR ART)




FIG. 3
(PRIOR ART)




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9






FIG. 10



[illegible]

FIG. 13 is a perspective view of a system 111 including a first cylindrical component 38, a second cylindrical component 112, a rectangular component 40, and a rectangular component 42. The first cylindrical component 38 is connected to the rectangular component 40 by a line 46. The second cylindrical component 112 is connected to the rectangular component 40 by a line 114. The rectangular component 42 is connected to the rectangular component 40 by a line 115. The rectangular component 40 is connected to the rectangular component 42 by a line 66.




FIG. 13




FIG. 15




FIG. 16

FIG. 17 is a schematic diagram of an optical system 150. The system includes a light source 38, a lens 46, a beam splitter 80, a mirror 42, a lens 58, a beam splitter 66, a lens 40, a mirror 52, a lens 120, a lens 152, a lens 118, and a detector 50. Light from the source 38 passes through the lens 46 and the beam splitter 80. It is then reflected by the mirror 42 and passes through the lens 58. The light then passes through the beam splitter 66, which splits it into two paths. One path goes through the lens 40 and the mirror 52, and the other path goes through the lens 120. Both paths then pass through the lens 152 and the lens 118, and are detected by the detector 50.




FIG. 17

DECLARATION FOR PATENT APPLICATION

As the below-named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated next to my name. I believe I am the original, first and sole inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled: **METHOD AND APPARATUS FOR REDUCING LASER SPECKLE USING POLARIZATION AVERAGING**. The specification of which is attached hereto. I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims. I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, Section 1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

Priority Claim

Yes No

--	--

Number

Country

Day/Month/Year Filed

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

Application Serial No.

Filing Date

Status: Patented, Pending, Abandoned

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of First Joint Inventor: Jahja I. Trisnadi

Inventor's Signature: Jahja I. Trisnadi

Date

4 Feb 2000

Residence: 21800 San Fernando Ave., Cupertino, CA 95014

Citizenship: Indonesia

Post Office Address: 21800 San Fernando Ave., Cupertino, CA 95014

Attorney Docket No.: PATENT
SLM-04300

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:) Group:
Jahja I. Trisnadi) Art Unit:
Serial No.:) Examiner:
Filed: herewith) **POWER OF ATTORNEY BY ASSIGNEE**
For: **METHOD AND APPARATUS FOR**)
REDUCING LASER SPECKLE USING)
POLARIZATION AVERAGING)

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

Silicon Light Machines, Assignee of the above-identified application by Assignment dated _____ hereby appoints the members of the firm of HAVERSTOCK & OWENS LLP, a firm including Thomas B. Haverstock (Reg. No. 32,571) and Jonathan O. Owens (Reg. No. 37,902) 260 Sheridan Avenue, Suite 420, Palo Alto, California 94306, telephone: (650) 833-0160, facsimile: (650) 833-0170, as its attorneys with full power of substitution to prosecute this application and to transact all business in the Patent and Trademark Office in connection therewith.

Please direct all correspondence regarding this application to the following:

Thomas B. Haverstock
HAVERSTOCK & OWENS LLP
260 Sheridan Avenue, Suite 420
Palo Alto, California 94306
Telephone: (650) 833-0160
Facsimile: (650) 833-0170

I hereby certify that the Assignment document filed with the application or filed subsequent to the filing date of the application, has been reviewed and I hereby certify that, to the best of my knowledge and belief, title is with **Silicon Light Machines**.

Silicon Light Machines

Dated: 2/4/00

By: David B. Corbin
Name: David B. Corbin
Title: President